


ANSI Type JX Thermocouple Extension Wire

Duplex construction—ANSI color code—White positive/Red negative— Black Over All

“JX” Thermocouple Extension Wire — Stocked on 100 and 250 Foot Spools



TC Type	Wire Type	Insulation	Insulation Temperature Limits (°F/°C)	Nominal Overall Dimensions (inches)	Part Number	
					100 Foot Spool	250 Foot Spool
JX	20 Gauge Solid	PVC	221/105	.092 x .154	TCWR-1027	TCWR-1031
JX	20 Gauge Stranded	PVC	221/105	.098 x .166	TCWR-1041	TCWR-1073
JX	24 Gauge Solid	PVC	221/105	.080 x .130	TCWR-1042	TCWR-1074
JX	24 Gauge Stranded	PVC	221/105	.084 x .138	TCWR-1043	TCWR-1075
JX	20 Gauge Solid	PVC with Shield & Drain	221/105	.169 Diameter	TCWR-1055	TCWR-1057


“JX” Thermocouple Extension Wire — Order Length Required (50 Foot Minimum)

B & S ga.	Wire Type	Insulation Over All	Insulation Each Conductor	Maximum Temp.		Nominal Overall Dimensions (inches)	Part Number
				°F	°C		
16	Solid	Polyvinyl (PVC)	Polyvinyl (PVC)	221	105	.111 x .192	TCW-102-105
16	Solid	PVC/twisted w/ alum Mylar tape shield & bare drain wire	Polyvinyl (PVC)	221	105	.207 x round	TCW-102-106

ANSI Type KX Duplex Construction Insulated Thermocouple Extension Wire

ANSI color code—Yellow positive/Red negative— Yellow Over All

“KX” Thermocouple Extension Wire — Stocked on 100 and 250 Foot Spools



TC Type	Wire Type	Insulation	Insulation Temperature Limits (°F/°C)	Nominal Overall Dimensions (inches)	Part Number	
					100 Foot Spool	250 Foot Spool
KX	20 Gauge Solid	PVC	221/105	.092 x .154	TCWR-1026	TCWR-1030
KX	20 Gauge Stranded	PVC	221/105	.098 x .166	TCWR-1044	TCWR-1076
KX	24 Gauge Solid	PVC	221/105	.080 x .130	TCWR-1045	TCWR-1077
KX	24 Gauge Stranded	PVC	221/105	.084 x .138	TCWR-1046	TCWR-1078
KX	20 Gauge Solid	PVC with Shield & Drain	221/105	.169 Diameter	TCWR-1056	TCWR-1058

“KX” Thermocouple Extension Wire — Order Length Required (50 Foot Minimum)

B & S ga.	Wire Type	Insulation Over All	Insulation Each Conductor	Maximum Temp.		Nominal Overall Dimensions (inches)	Part Number
				°F	°C		
20	Stranded (7/28)	PVC/twisted w/alum. mylar tape shield & bare drain wire	Polyvinyl (PVC)	221	105	.181 round	TCW-117-105