
MI Cable Thermocouple Assemblies



Style MTA6 Connection Head with 1/2" NPT Hex Nipple (Stock)



Ordering a Stock MTA6 Thermocouple

(Thermocouples not available from stock can be custom manufactured—see page 14-23)

TEMPCO stocks **MTA6 style Thermocouples** in type J and K in the standard lengths listed in the following two tables. These thermocouples have a 1/2" NPT SS process connection with a standard die cast aluminum head (Type A)

Order a stock unit from the tables after completing the ordering code with the Junction Type Code from Box 4 below.

Stock Type J - 316 SS Sheath

	"L" Dimension					
Diameter	6"	12"	18"	24"		
0.125"	ST6JF06	ST6JF12	ST6JF18	ST6JF24		
0.188"	ST6JG06	ST6JG12	ST6JG18	ST6JG24		
0.250"	ST6JH06	ST6JH12	ST6JH18	ST6JH24		

Stock Type K — Alloy 600 Sheath

	"L" Dimension					
Diameter	6"	12"	18"	24"		
0.125"	ST6KF06	ST6KF12	ST6KF18	ST6KF24		
0.188"	ST6KG06	ST6KG12	ST6KG18	ST6KG24		
0.250"	ST6KH06	ST6KH12	ST6KH18	ST6KH24□		

Stock Modification

Above stocked items can be cut to desired length and junctioned for fast delivery. For lengths other than listed in table above, complete the Code Number below.

Ordering Code: ST6 - 1 2 3 4

Calibration BOX 1
ANSI Standard
Tolerances
J K

Diameter BOX 2 **F** = .125" **G** = .188" **H** = .250"

"L" Dimension BOX 3
06", 12", 18", 24" Stock Lengths
For other lengths specify in inches.

Junction BOX 4

G = Grounded
U = Ungrounded
E = Exposed

★ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.