


### Series CRB Curved Face Ceramic E-Mitters – Size: 60 mm × 245 mm (2.36" × 9.65")



Color shown is  
rose (cold) to grey (hot)

#### Optional Features

- \* *Additional Power or Thermocouple Lead Lengths (page 7-23)*
- \* *Two-Piece Wave Mounting Clip (page 7-14)*
- \* *Reflectors and Other Accessories (pages 7-20 through 7-23)*
- \* *Arrays and Power/Temperature Control Panels (start on page 7-15)*

#### Standard (Non-Stock) CRB E-Mitters

E-Mitters listed have 3.50" ceramic bead insulated leads, #8-10 spade terminals, and a one-piece spring clip for mounting.

Wattage	Voltage	Color	Watt Density*		Heater Body Temp.**		Part Number	
			(W/in <sup>2</sup> )	(W/cm <sup>2</sup> )	(Typical Operating) °F	°C	Without Thermocouple	With Type K Thermocouple
150	220/240	Rose to Grey	6.48	1.00	560	293	CRB10216	CRB10217
150	220/240	White	6.48	1.00	560	293	CRB00216	CRB00217
250	220/240	Rose to Grey	10.80	1.67	756	402	CRB10006	CRB10008
250	220/240	White	10.80	1.67	756	402	CRB00006	CRB00008
400	220/240	Rose to Grey	17.27	2.68	942	506	CRB10014	CRB10016
400	220/240	White	17.27	2.68	942	506	CRB00014	CRB00016
650	120	Rose to Grey	28.07	4.35	1156	624	CRB10020	CRB10022
650	120	White	28.07	4.35	1156	624	CRB00020	CRB00022
650	220/240	Rose to Grey	28.07	4.35	1156	624	CRB10023	CRB10025
650	220/240	White	28.07	4.35	1156	624	CRB00023	CRB00025
650	480	Rose to Grey	28.07	4.35	1156	624	CRB10088	CRB10165
650	480	White	28.07	4.35	1156	624	CRB00088	CRB00165
1000	120	Rose to Grey	43.18	6.69	1420	771	CRB10028	CRB10030
1000	120	White	43.18	6.69	1420	771	CRB00028	CRB00030
1000	220/240	Rose to Grey	43.18	6.69	1420	771	CRB10031	CRB10033
1000	220/240	White	43.18	6.69	1420	771	CRB00031	CRB00033
1000	480	Rose to Grey	43.18	6.69	1420	771	CRB10089	CRB10045
1000	480	White	43.18	6.69	1420	771	CRB00089	CRB00045

### Semi-Finished Stock CRB E-Mitters (Five Business Day Manufacturing)

Semi-Finished Series CRB E-Mitters listed below are stocked ready for color glazing. Colors available are metamorphing rose (cold) to grey (hot), traditional white, metamorphing yellow (cold) to orange (hot), and black.

They can be terminated with beaded leads up to 6" long with spliced-on lead wire for lengths beyond 6" and straight, ring, or spade terminals. Some are available with a thermocouple (any length).

A part number will be assigned at time of order.

Wattage	Voltage	Watt Density*		Heater Body**		Optional Thermocouple (Any Length)
		(W/in <sup>2</sup> )	(W/cm <sup>2</sup> )	Temperature (Typical) °F	°C	
400	230	17.27	2.68	942	506	N/A
650	230	28.07	4.35	1156	624	Type K
650	480	28.07	4.35	1156	624	N/A
1000	230	43.18	6.69	1420	771	Type K
1000	480	43.18	6.69	1420	771	Type J or K

**CRB Ordering Information** (See page 7-2)